

LIGHTING FIXTURE SCHEDULE

SYMBOL	TAG	DESCRIPTION	MANUFACTURER	LAMPS	REMARK
	S 72	LUMINAIRE: SOLARONE PERFORMANCE PRO 190 SOLAR LIGHTING SYSTEM, 1.2kWh, LFP BATTERY CAPACITY, DUAL DIAMETER ALUMINUM POLE, 10" TO 7" DIAMETER AND 27.6' HEIGHT, BIRD GUARD, 32LED 72W LAMP, 3000°K, TYPE III. COLOR-BLACK. POLE & ARM: 28' T6 POWDER COATED SPUN ALUMINUM POLE, WITH 4' SIDE MAST ARM WITH 1.5' RISE AND SIMPLEX MOUNT.	FIXTURE: SOLARONE RFM LFP CAT#: RFM-72W32LED3K-G2-R3M-2M724-P190GP-TP13-(PI-2B50RL-MPT15-24V)-R7.0x280-4SR-BK	72W 32LED 3000°K	NEW FIXTURE AND POLE


POLE AND EQUIPMENT SCHEDULE

POLE No.	TYPE OF POLE	LUMINAIRE VOLTAGE/WATTAGE	VEHICLE SIGNAL					PEDESTRIAN SIGNAL			REMARKS
			No.	TYPE	MOUNTING	VISORS	LOUVERS	No.	TYPE	MOUNTING	
①	28' SOLAR POWERED POLE WITH LUMINAIRE	S 72									TOP MOUNT SOLAR POWERED FOR STREETLIGHT
②	1-A (15')		22 61	①	SIDE MOUNT SIDE MOUNT						TOP MOUNT SOLAR POWERED FOR FLASHING BEACON PEDESTRIAN PUSH BUTTON ②
③	1-A (15')		21 62	①	SIDE MOUNT SIDE MOUNT						TOP MOUNT SOLAR POWERED FOR FLASHING BEACON PEDESTRIAN PUSH BUTTON ②
④	28' SOLAR POWERED POLE WITH LUMINAIRE	S 72									TOP MOUNT SOLAR POWERED FOR STREETLIGHT

SHEET NOTES:

- ① CONTRACTOR TO INSTALL CITY-FURNISHED JSF TECHNOLOGIES AB-9407 SOLAR DUAL SIDED RECTANGULAR RAPID FLASHING BEACON ASSEMBLY
- ② CONTRACTOR TO INSTALL CITY-FURNISHED ASSEMBLY R62E AND PEDESTRIAN PUSH BUTTON ON POLE
- ③ 1-2" PVC CONDUIT FOR RRFB IN SAME TRENCH
- ④ 1-1.5" GRSC CONDUIT FOR LUMINAIRE IN SAME TRENCH
- ⑤ CITY FORCES TO INSTALL ONLY THE NEW MUTCD SIGNS W11-2 AND W16-7P SO THAT THE SIGNS ARE INSTALLED ON BOTH SIDES OF POLE WITH ARROWS POINTING TOWARD CROSSWALK

PHASE DIAGRAM



SFMTA SD: Daniel Carr & Soroush Roback
SFMTA Signal Shop: Ben Murphy
BAL: Angel Martinez
SFPW: Robert Mau
RPD: Monica Scott

Activated on 10/8/2021 at 9:37AM

PHASE SEQUENCE

FY	VISITACION AVENUE. (EB & WB) - Ø2 & Ø6
----	--

